

## 1.0 PREFACE

ESS 7.0/9.0 is a new modular lithium-ion based energy storage system, which stores the surplus of the collected solar energy for later demand. Energy can either be directed into the storage system or be fed into the public grid via an inverter.

Energy is available as required: in the evening, at night, or on a cloudy day.

With the ESS 7.0/9.0 System, consumers of solar power become more independent from electricity prices and use their home-made eco-electricity when they need it.

## ADVANTAGES

- Store during the day; use day and night
- Independent from daylight and public grid
- Economic, cost-cutting and ecofriendly
- Lightweight, save and space saving
- Modular installation: the storage capacity can be adapted to your needs
- Subsidized by the Federal Government of Germany: KfW-Program 275

## TECHNICAL PROPERTIES

- Powerful energy storage system
- New lithium-ion technology: a 7 year warranty covering the system's current value
- High efficiency: 95 %
- High discharge depth: 80 % DOD (Depth of Discharge)
- Durable: 5,000 full cycles
- Parallel installation of max. 6 modules possible
- High operational safety

## SAFETY MEASURES

- Direct current relay and 2nd protection (chemical fuse) for a redundant battery cut-off
- Overvoltage and low voltage monitoring for each cell string with redundant battery cut-off
- Temperature monitoring for each cell string and current interrupt device (CID) in each cell
- Protection against a reboot after deep discharge or any other serious error
- No insecure parallel connection of cells without current interrupt device (CID) in each cell
- Active current control as a function of cell voltage and temperature (derating)
- Closed metal housing

## 2.0 TECHNICAL PROPERTIES OF A SINGLE MODULE



ESS 7.0 and ESS 9.0

GENERAL PROPERTIES	ESS 7.0	ESS 9.0
Energy (nom./real)	6.74 kWh/5.39 kWh	8.5 kWh/6.8 kWh
Nominal voltage	55.5 V	54.0 V
Charge end voltage	61.5 V	61.5 V
Discharge end voltage	45.0 V	45.0 V
Capacity (nom./real)	121.5 Ah/ 97.2 Ah	156.6 Ah/125.3 Ah
Max. charge	90 A	120 A
Max. discharge current	300 A ( 3 sec.)	300 A ( 3 sec.)
Max. discharge power	18 kW*	18 kW*
Weight	95 kg	97 kg
Dimensions (mm) W x H x D	638 x 421 x 487 mm	638 x 421 x 487 mm
Communication	CAN – SMA ready	CAN – SMA ready
Battery chemistry	Li-Ion NMC	Li-Ion NMC
Discharge depth	80% DOD	80% DOD
Full cycles	5,000	5,000
Battery Management System	Monitoring of cell voltage, cell temperature, current, derating and passive balancing	

### PERFORMANCE DATA

Energy density (weight)	71 Wh/kg	87.6 Wh/kg
-------------------------	----------	------------

### DEVELOPED ACCORDING TO THE STANDARDS AND USER GUIDELINES FOR STATIONARY ENERGY STORAGE SYSTEMS

- VDE-AR-E 2510-50
- VDE-AR-E 2510-2
- DIN EN 62619 (draft)
- FNN note
- 04/2016 version

### USER INFORMATION

- Discharge temperature (cells): 2 °C to +45 °C
- Charge temperature (cells): 2 °C to +45 °C
- Recommended storage temperature: 10 °C to 25 °C
- Self discharge (cells): ca. 2 % per year
- Max. parallel connection (of batteries): 6 (additional hardware required)
- Protection class: IP 21
- European Conformity (CE): yes
- UN-test 38.3: yes
- Warranty: 2 year warranty (optional extendable)

\*depends on the respective inverter